

HISTORY KEPT YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>		ILLINOIS HIGHWAY INFORMATION SYSTEM STRUCTURE INFORMATION AND PROCEDURE MANUAL	
NBIS REQUIRED YES <input checked="" type="checkbox"/> NO <input type="checkbox"/>		ITEM NAME SIDEWALK WIDTH ON (RIGHT/LEFT)	ITEM NO. 50A/50B PAGE 1 of 1 EFF. DATE 07/01/02
		ISIS	MMIS
RESPONSIBLE FOR UPDATE	District Program Development		N/A
STRUCTURES	All		N/A
UPDATE SCREENS	(1) Add New Structure (3) General Inventory 2		N/A
INQUIRY SCREENS	(3) Inventory Data 3		(1) Inventory Data 3 of 3

DESCRIPTION AND PURPOSE OF ITEM

This item applies to sidewalks on a structure. A sidewalk is that portion of a bridge floor, usually elevated above the roadway, which is provided for the convenient and safe passage of pedestrians. Brush or safety curbs less than 18 inches in width are not to be considered sidewalks.

The sidewalk width is the clear width measured at right angles to the longitudinal centerline of the structure. This is the horizontal distance measured from the inside face of the structure railing, parapet, truss or girder to the bottom edge of the sidewalk curb or, if present, to the sidewalk face of a railing separating the sidewalk from the roadway.

"Right" is defined as the sidewalk adjacent to the traffic lanes in the southbound or eastbound directions. This is represented by Item 50A. "Left" is defined as the sidewalk adjacent to the traffic lanes in the northbound or westbound directions. This is represented by Item 50B.

Refer to Appendix C, Figure 4.1 & 8.1.

CODE AND SCREEN ENTRY INSTRUCTIONS

A three-digit field, to one decimal position, right justified.

Enter the width to the nearest tenth of a foot, filling leading spaces with zeros when applicable.

The width entered must be a minimum of 1.5 feet.

Leave blank if no sidewalk exists in the applicable direction.